














PROBE	MATERIAL	APPLICATION	REFERENCE												
<p>½ SPHERE</p> 	<p>Stainless Steel 316 L</p>	<p>Type of measurement : - Compression - Relaxation - Cycle</p> <p>Type of Product : - Paste, Foam, Gel - Cheese</p> <p>Focus : - Elasticity Measure</p>	<table border="1"> <tr> <td>Diameter</td> <td>30 mm</td> </tr> <tr> <td colspan="2">REF: 0029-0055</td> </tr> </table> <table border="1"> <tr> <td>Diameter</td> <td>40 mm</td> </tr> <tr> <td colspan="2">REF: 0029-0058</td> </tr> </table>	Diameter	30 mm	REF: 0029-0055		Diameter	40 mm	REF: 0029-0058					
Diameter	30 mm														
REF: 0029-0055															
Diameter	40 mm														
REF: 0029-0058															
<p>PLATE</p> 	<p>Stainless Steel 316 L</p>	<p>Type of measurement: - Compression, - Traction, - Cycle</p> <p>Type of Product: - Cream, Cheese, Gel - Grease, Coating</p> <p>Focus: - Adhesivness Measure, - Low thickness</p>	<table border="1"> <tr> <td>Diameter</td> <td>50 mm</td> </tr> <tr> <td colspan="2">REF: 0029-0059</td> </tr> </table> <table border="1"> <tr> <td>Diameter</td> <td>34 mm</td> </tr> <tr> <td colspan="2">REF: 0029-0060</td> </tr> </table>	Diameter	50 mm	REF: 0029-0059		Diameter	34 mm	REF: 0029-0060					
Diameter	50 mm														
REF: 0029-0059															
Diameter	34 mm														
REF: 0029-0060															
<p>CYLINDRE</p> 	<p>Stainless Steel 316 L</p> <p>Plexiglass</p>	<p>Type of measurement: - Compression, - Cycle</p> <p>Type of Product: - Gelatine, Cream, - Paste, Tooth paste - Stewed fruit</p> <p>Focus: - Bloom test, - Consistency</p>	<table border="1"> <tr> <td>Diameter</td> <td>25 mm</td> </tr> <tr> <td>Height</td> <td>40 mm</td> </tr> <tr> <td colspan="2">REF: 0029-0061</td> </tr> </table> <p>Bloom cylinder</p> <table border="1"> <tr> <td>Diameter</td> <td>12.7 mm</td> </tr> <tr> <td>Height</td> <td>30 mm</td> </tr> <tr> <td colspan="2">REF: 0029-0047</td> </tr> </table>	Diameter	25 mm	Height	40 mm	REF: 0029-0061		Diameter	12.7 mm	Height	30 mm	REF: 0029-0047	
Diameter	25 mm														
Height	40 mm														
REF: 0029-0061															
Diameter	12.7 mm														
Height	30 mm														
REF: 0029-0047															

<p style="text-align: center;">CONE</p> 	<p style="text-align: center;">Stainless Steel 316 L</p>	<p>Type of measurement: - Compression</p> <p>Type of Product: - Grease, Butter, Dough - Crust</p> <p>Focus: - Crispy Force, - Consistency</p>	<p style="text-align: center;">Cône 20°</p> <table border="1" style="width: 100%;"> <tr><td>Diameter</td><td>25 mm</td></tr> <tr><td>Cone angle</td><td>20°</td></tr> <tr><td colspan="2">REF: 0029-0063</td></tr> </table> <p style="text-align: center;">Cône 45°</p> <table border="1" style="width: 100%;"> <tr><td>Diameter</td><td>30 mm</td></tr> <tr><td>Cone angle</td><td>45°</td></tr> <tr><td colspan="2">REF: 0029-0062</td></tr> </table>	Diameter	25 mm	Cone angle	20°	REF: 0029-0063		Diameter	30 mm	Cone angle	45°	REF: 0029-0062					
Diameter	25 mm																		
Cone angle	20°																		
REF: 0029-0063																			
Diameter	30 mm																		
Cone angle	45°																		
REF: 0029-0062																			
<p style="text-align: center;">NEEDLE</p> 	<p style="text-align: center;">Stainless Steel 316 L</p>	<p>Type of measurement: - Compression</p> <p>Type of Product: - Sausage, Cheese - Confectionery, Tablet, - Soap, Bitumen, - Lipstick</p> <p>Focus: - Penetrometry, - Inside Consistency</p>	<table border="1" style="width: 100%;"> <tr><td>Diameter</td><td>2 mm</td></tr> <tr><td colspan="2">REF: 0029-0064</td></tr> <tr><td>Diameter</td><td>3 mm</td></tr> <tr><td colspan="2">REF: 0029-0065</td></tr> <tr><td>Diameter</td><td>4 mm</td></tr> <tr><td colspan="2">REF: 0029-0056</td></tr> <tr><td>Diameter</td><td>6 mm</td></tr> <tr><td colspan="2">REF: 0029-0066</td></tr> </table>	Diameter	2 mm	REF: 0029-0064		Diameter	3 mm	REF: 0029-0065		Diameter	4 mm	REF: 0029-0056		Diameter	6 mm	REF: 0029-0066	
Diameter	2 mm																		
REF: 0029-0064																			
Diameter	3 mm																		
REF: 0029-0065																			
Diameter	4 mm																		
REF: 0029-0056																			
Diameter	6 mm																		
REF: 0029-0066																			
<p style="text-align: center;">BLEND</p> 	<p style="text-align: center;">Stainless Steel 316 L</p>	<p>Type of measurement: - Compression</p> <p>Type of Product: - Fruit, Vegetable, - Sausage, Cheese, - Lipstick</p> <p>Focus: - Breaking Force, - Knack</p>	<table border="1" style="width: 100%;"> <tr><td>Length</td><td>25 mm</td></tr> <tr><td>Angle α</td><td>60°</td></tr> <tr><td colspan="2">REF: 0029-0067</td></tr> </table>	Length	25 mm	Angle α	60°	REF: 0029-0067											
Length	25 mm																		
Angle α	60°																		
REF: 0029-0067																			
<p style="text-align: center;">DOUBLE CONE</p> 	<p style="text-align: center;">Stainless Steel 316 L</p>	<p>Type of measurement: - Compression</p> <p>Type of Product: - Lubricant Grease, - Jam, Fruit, - Thick Material</p> <p>Focus: - Inside Consistency - Penetrometry</p>	<table border="1" style="width: 100%;"> <tr><td>Diameter</td><td>65 mm</td></tr> <tr><td>Angle α_1</td><td>90°</td></tr> <tr><td>Angle α_2</td><td>30°</td></tr> <tr><td colspan="2">REF: 0029-0057</td></tr> </table>	Diameter	65 mm	Angle α_1	90°	Angle α_2	30°	REF: 0029-0057									
Diameter	65 mm																		
Angle α_1	90°																		
Angle α_2	30°																		
REF: 0029-0057																			

PROBES AVAILABLE ON REQUEST:

-  KRAMER Cell
-  OTTAWA Cell
-  VOLODKEVICH Cell
-  3 Point Bending Cell
-  Extrusion Cell
-  Traction grips

WE ARE AT YOUR DISPOSAL TO REALIZE ALL OTHER PROBE YOU NEED.